


Coating PLATE for Offset Coating

PREMIUM ALL IN ONE | Rubber Surface | Polyester Carrier

PRODUCT FEATURES

- Smooth surface provides optimum coating transfer of water
 - based (aqueous) and UV coating applications
- · No ink build up surface technology
- Excellent for high speed presses
- Easy cutting (CAD & manual) & stripping technology
- Superior for Gloss, Matt and Soft Touch coatings
- Bi-Directional-Cutting
- · Suitable for food packaging
- · High delamination resistance even in long-run UV

PRODUCT PROFILE



1 = not suggested

2 = suitable

3 = excellent

4 = optimum

TECHNICAL SPECIFICATION

Surface	Rubber
Juliace	Rubbei

(Rubber / Polymer)

Micro-Hardness

60° Shore A

Thickness 1.15 mm (0.045") (Tolerance +/- 0.03mm) 1.35 mm (0.053") 1.95 mm (0.077")

Stripping Depth 1.15 mm = 0.80 mm (0.031")

1.35 mm = 1.00 mm (0.040") 1.95 mm = 1.60 mm (0.063")

·

Roll width 1080 mm (42 1/2")

1280 mm (52") 1480 mm (58 1/4") 1580 mm (62 1/4")

Roll length 30m / 50m

Carrier Polyester PET (0.35 mm)

(Polyester PET / Fabric)

CROSS SECTION

